



Technical Specifications for BreatheEZ Sheathing Tape

White Sheathing Tape

Product Description

A thin, strong, white polypropylene film coated with an aggressive cold weather acrylic adhesive system. This system was specially formulated to have excellent performance characteristics at both sub-freezing temperatures and elevated temperatures along with good quick stick for ease in applying.

Applications:

Used primarily as a closure system and vapor seal on the seams of all exterior sheathing materials and BreatheEZ Housewrap. Can also be used to repair rips, punctures and tears on interior vapor barrier systems. This tape can be applied to door and window flanges, sill plates, corners, and joints to improve air tightness.

Technical Data

Property	Imperial	Metric
Thickness:	3 mils (.003")	0.076 mm
Adhesion: Peel:		
	Polyethylene 16.0 oz/inch	4.6 N/2.5 cm
	Stainless Steel 65.0 oz/inch	18.5 N/2.5 cm
Shear: 96 hrs @	2.2 psi	15.2 kPa
Hot Shear: 20 min @	150°F/2.2 psi	66°C/15.2 kPa
Tensile:	20 lbs/inch width	91 N/2.5 cm
Elongation:	136%	136%
WVTR (100°F/90% RH)	0.27 grams/100 in ²	
Shelf Life:	Recommend one year from date of receipt by customer when stored under optimum conditions (70°F, 50% RH)	

IMPORTANT INFORMATION:

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties and are not intended to be used as specifications for defined applications. User must determine the product suitability for the end use application and assume all risks and liabilities.